


EB Series

Product Description

SALIRONE innovates not only the revolution & green composite material, but also brings durability and characteristics together with a variety of colors & texture, that creates a even better elegant fashion world.



Product Features

- · Safe & Soft skin touch
- · Antiallergic
- · Anti-bacterial & Mould proof
- · High/Low Temperature Resistance
- · Colorful and Stylish
- Green protective and environmental friendly
- · 0% solvent
- · Extraordinary low VOC
- · Green process
- Insulation

Color and texture

Custom colors and textures are available upon request.

Typical Applications

Electronics materials. Accessories...

$\mathcal{C}_{\mathbf{I}}$	200	ritic	iter	On
\sim		אוווע	cati	ULI

Width: 1370mm
Put-up: 50m R.O.T.
Substrate Material Type: Polyester fibre
Substrate Material Thickness: 0.3~0.6mm

CHARACTERISTICS		VALUE	
Tensile Force			
	longitudinal	≥420N	
	Transverse	≥330N	
Tensile Elongation			
	longitudinal	≥45%	
	Transverse	≥45%	
Tear Force			
	longitudinal	≥16N	
	Transverse	≥80N	
RoHS 2.0		Comply	
REACH 175 Item		Comply	

^{*} All data value based on substrate material: One side brush, thickness is 0.35mm.

CHARACTERISTICS		VALUE	
Tensile Force			
	longitudinal	≥260N	
	Transverse	≥200N	
Tensile Elongation			
	longitudinal	≥25%	
	Transverse	≥25%	
Tear Force			
	longitudinal	≥11N	
	Transverse	≥25N	
RoHS 2.0		Comply	
REACH 175 Item		Comply	

^{*} All data value based on substrate material: Two side brush, thickness is 0.4mm.

^{*} All data shown only for basic reference, and not as specification or warranty.

^{*} All data shown only for basic reference, and not as specification or warranty.

Rev.: A00

CHARACTERISTICS		VALUE	
longitudinal		≥170N	
Transverse		≥170N	
Tensile Elongation			
longitudinal		≥80%	
Transverse		≥80%	
longitudinal		≥12N	
Transverse		≥20N	
		Comply	
REACH 175 Item		Comply	
	longitudinal Transverse tion longitudinal Transverse longitudinal Transverse	longitudinal Transverse tion longitudinal Transverse longitudinal Transverse	longitudinal ≥170N Transverse ≥170N tion ≥80% Iongitudinal ≥80% Iongitudinal ≥12N Transverse ≥20N Comply

 $[\]star$ All data value based on substrate material : Ultra fine Velvet, thickness is 0.4mm.

 $[\]star$ All data shown only for basic reference, and not as specification or warranty.

CHARACTERISTICS VALUE			
Tensile Force			
	longitudinal	≥230N	
	Transverse	≥230N	
Tensile Elonga	tion		
	longitudinal	≥21%	
	Transverse	≥21%	
Tear Force			
	longitudinal	≥50N	
	Transverse	≥25N	
RoHS 2.0		Comply	
REACH 175 Item		Comply	

 $[\]star$ All data value based on substrate material : White fabric, thickness is 0.53mm.



 $[\]star$ All data shown only for basic reference, and not as specification or warranty.